

Subwoofer SMS G15

Amplifier 1000 W	1000 W
Peak Output Current	30 A
THD+N	0,003 %
Dynamic Range	120 dB
Power Consumption, Standby	0,3 W
Ethernet AVB	100 Mbit/s, Fast Ethernet
Netzwerk Input	RJ-45 / Cat 5
Switch	2 port Fast Ethernet Switch, AVB zertifiziert
Streaming Technology	Ethernet, AVB certified 500 ns synchronicity 2 ms latency 2 streams / 8 channels per stream 48/96 kHz
Command & Control	UNOS
DSP Channels	2
Input Sensitivity / Impedance	8 dBu / 20 KOhms
Analogue Inputs	2 x XLR female (+ cinch adapter)
Technology	sealed bass cabinet
Max SPL	119 dBSPL con. 124 dBSPL peak
Frequency Range	18 Hz – 100 Hz
Subwoofer LF	custom made 38 cm driver with solid aluminium basket and extremely efficient Neodymium magnet 10 cm voice coil 36 mm linear cone excursion
Dimensions (H/W/D)	50 x 42,5 x 46 cm
Weight	30 kg
Cabinet	MDF with 44 mm baffle, internally strengt- hened, durable black textured paint piano lacquer black and white differing colours on request

